

GEYSER® Garden 500 Self-draining garden valve No. 40185.00

Tap valve manufactured for non-drinking water use outdoors. Properly installed, the garden valve will be frost-free.

Installation: It is the installer's responsibility to ensure that the installation is legal according to applicable standards.

Installation of the garden valve must be carried out by an authorised installer. The inner part of the

garden valve must always be in a frost-free environment.

Mounting: The garden valve is connected to the 15mm pipe installation. If the installation is soft or semi-hard

pipes, support bushings must be used.

Contents: Garden valve for wall penetration. Handle for fixed mounting. Key for safety mounting. Check valve.

Vacuum valve.

Use: The garden valve is self-draining when closing. After closing the handle or key, a little water runs out of

the drain hole.

Material: Fittings and valve: CR brass. Tube: Copper TP2. Flange: Stainless steel 304. Handle: Zamak. Key: ABS

Flow rate: Max 22 I/min according to available local water pressure.

Temperature: Recommended water temperature 10 C°.

Test pressure: 16 bar
Operating: 1-6 bar
Acoustics: Group 1

Warranty: 5-year warranty against dripping and manufacturing defects.

Out of Misuse, incorrect installation, damage after frost, dirt and calcification.

Warranty: Installation without following instructions.

Maintenance: The garden valve requires no daily maintenance.

Check the entire installation for tightness at least every 6 months, or as needed.

Certificate: RISE SC1005-15. Owner: SCE Technology.

Test norm: EN200:2023. NKB12

Test reports: RISE: 2244/89. SC1535-11. 0100115-1331971.

DTI: 841832-6. 918849-1. 263752-1

SP: 5P02267. 5P02267-01

Documents: Test reports are confidential and will not be shared.

RISE, VVS-Trading and SCE Technology vouch for the validity of the documents.

Marking: GEYSER® EAGLE

Manufacturer: GEYSER® VVS-Trading. EAGLE: SCE Technology.